


### LED TUBE QUOTATION

PICTURE	Model No	Length	Diameter	Input Voltage	led type and brand	Description	Luminous Flux (lm)	Unit Price \$ ( EXW,NO TAX )
	GL-T8-96D11W-60	60cm	φ 26mm	AC85-265V	SMD3014, Epistar	96leds.11W, aluminum heat sink body + PC cover	1000±5%	5,5
	GL-T8-106D12W-120	120cm	φ 26mm	AC85-265V	SMD3014, Epistar	106leds.12W, aluminum heat sink body + PC cover	1200±5%	7,7
	GL-T8-178D18W-120	120cm	φ 26mm	AC85-265V	SMD3014, Epistar	178leds.18W, aluminum heat sink body + PC cover	2000±5%	9,02
	GL-T8-120D8W-60	60cm	φ 26/30mm	AC85-265V	SMD3528, Epistar	120leds.8W, aluminum heat sink body + PC cover	1000±5%	5,5
	GL-T8-144D10W-60	60cm	φ 26/30mm	AC85-265V	SMD3528, Epistar	144leds.10W, aluminum heat sink body + PC cover	1100±5%	6,6
	GL-T8-216D14W-120	120cm	φ 26/30mm	AC85-265V	SMD3528, Epistar	216leds.14W, aluminum heat sink body + PC cover	1400±5%	8,25
	GL-T8-240D16W-120	120cm	φ 26/30mm	AC85-265V	SMD3528, Epistar	240leds.16W, aluminum heat sink body + PC cover	1600±5%	9,35
	GL-T8-288D20W-120	120cm	φ 26/30mm	AC85-265V	SMD3528, Epistar	288leds.20W, aluminum heat sink body + PC cover	2000±5%	9,9
	GL-T8-360D25W-150	150cm	φ 26/30mm	AC85-265V	SMD3528, Epistar	360leds.25W, aluminum heat sink body + PC cover	2500±5%	12,1

**Technical Data**

1. Power factor: 0.85 ~ 0.95
2. CRI(color rendering index) : >75Ra
3. PCB type: aluminum based PCB
4. 1000h light decay: less than 2%
5. Color temperature: warm white(2800-3500K)  
day white(4000-4500K)  
neutral white(6000-6500K)

**Remark:**

- A: The quotation is based on Ex-work, Shenzhen  
 B: Warranty: 3 year warranty for the above products from the delivery date  
 C: Delivery time: 20-25days after you pay for the deposit (2000pcs)  
 D: Installation: Remove the ballast and starter before install LED tube

